





DK158 Rhino-Rack VA, Aero, Euro & HD crossbar instruction

CONTROLLED


IDENTIFICATION CHART









VA crossbar



EURO crossbar



HD crossbar

			FRONT CROSSBAR						REAR CROSSBAR					
				 VA	 EURO	 HD			 VA	 EURO	 HD			
Vehicle	Date	Crossbar	Front Right Pad/ Clamp	Front Left Pad/ Clamp	Measurement strip length per side	Measurement strip length per side	Measurement Distance (x)	Foot plate arrow direction	Rear Right Pad/ Clamp	Rear Left Pad/ Clamp	Measurement strip length per side	Measurement strip length per side	Measurement Distance (x)	Foot plate arrow direction
Mazda 6 4dr Sedan (GH) 2nd Gen	2009 - 2013	1260mm	M366 SUB0153	M366 SUB0153	179mm	66mm	1006mm / 39,39/64"	OUT	M366 SUB0144	M366 SUB0144	179mm	66mm	1006mm / 39,39/64"	OUT
			Arrow FORWARD						Arrow FORWARD					



DK158 Rhino-Rack VA, Aero, Euro & HD crossbar instruction


CONTROLLED

Measurement A: CENTRE of door jamb to CENTRE arrow of leg foot plate.


Measurement B: CENTRE of Front leg foot plate arrow to CENTRE of Rear leg foot plate arrow.

Carrying capacity: Roof rack is rated to 75kg. Please refer to manufacturers handbook for your vehicles maximum roof load capacity. Always use the lower of the two figures.

If your vehicle is not listed on this fitting instruction please refer to your countries Rhino-Rack web site for the latest information.



Direction of Pad, Arrow and Foot Plates



VEHICLE	Date	Measurement A	Measurement B	Load Rating (includes racks 5kg/11lbs)
Mazda 6 4dr Sedan (GH) 2nd Gen	2009 - 2013	280mm / 11,1/32"	700mm / 27,9/16"	75kg / 165lbs