





DK226 Rhino-Rack VA, Aero, Euro & HD crossbar instruction


IDENTIFICATION CHART




VA crossbar



AERO crossbar







EURO crossbar







HD crossbar

FRONT CROSSBAR



REAR CROSSBAR



Vehicle	Date	Crossbar	Front Right Pad/ Clamp	Front Left Pad/ Clamp	Measurement strip length per side	Measurement strip length per side	Measurement Distance (x)	Foot plate arrow direction	Rear Right Pad/ Clamp	Rear Left Pad/ Clamp	Measurement strip length per side	Measurement strip length per side	Measurement Distance (x)	Foot plate arrow direction
Chevrolet Equinox LS SUV	2010 on	1180mm	M367 SUB0382	M367 SUB0382	185mm	130mm	938mm / 36,59/64"	OUT	M367 SUB0382	M367 SUB0382	182mm	127mm	932mm / 36,11/16"	OUT
			Arrow FORWARD						Arrow FORWARD					




DK226 Rhino-Rack VA, Aero, Euro & HD crossbar instruction

Measurement A: CENTRE of door jamb to CENTRE arrow of leg foot plate.


Measurement B: CENTRE of Front leg foot plate arrow to CENTRE of Rear leg foot plate arrow.

Carrying capacity: Roof rack is rated to 75kg. Please refer to manufacturers handbook for your vehicles maximum roof load capacity. Always use the lower of the two figures.

If your vehicle is not listed on this fitting instruction please refer to your countries Rhino-Rack web site for the latest information.



Direction of Pad, Arrow and Foot Plates



VEHICLE	Date	Measurement A	Measurement B	Load Rating (includes racks 5kg/ 11lbs)
Chevrolet Equinox LS SUV	2010 on	300mm / 11,13/16"	700mm / 27,9/16"	60kg / 132lbs