





Rhino Rack 2500 Series - DK484 nstruction

CONTROLLED


CROSSBAR IDENTIFICATION









VA crossbar



EURO crossbar



HD crossbar

			FRONT CROSSBAR						REAR CROSSBAR					
														
Vehicle	Date	Crossbar	Front Right Pad/Clamp	Front Left Pad/Clamp	Measurement strip length per side	Measurement strip length per side	Measurement Distance (x)	Foot plate arrow direction	Rear Right Pad/Clamp	Rear Left Pad/Clamp	Measurement strip length per side	Measurement strip length per side	Measurement Distance (x)	Foot plate arrow direction
MG 3 5dr Hatch	05/17 -	1180mm	M367 SUB0369	M367 SUB0369	157mm	102mm	882mm 34 3/4	OUT	M367 SUB0369	M367 SUB0369	157mm	102mm	882mm 34 3/4	OUT
			Pad Arrow FWD						Pad Arrow FWD					



Rhino Rack 2500 Series - DK484 nstruction

CONTROLLED


Measurement A: CENTRE of door jamb to CENTRE arrow of leg foot plate.

Measurement B: CENTRE of Front leg foot plate arrow to CENTRE of Rear leg foot plate arrow.

Carrying capacity: Roof rack is rated up to 75kg/165lbs. Please refer to manufacturers handbook for your vehicles maximum roof load capacity. Always use the lower of the two figures.


If your vehicle is not listed on this fitting instruction please refer to your countries Rhino-Rack web site for the latest information.

Direction of Pad Arrow and Foot Plate Arrow



FRONT

REAR



VEHICLE	Date	Measurement A	Measurement B	Load Rating up to (includes racks 5kg/ 11lbs)
MG3 5dr Hatch	05/17-	225mm / 8, 7/8"	700mm / 27,9/16"	75kg / 165lbs