





Rhino Rack 2500 Series - DK492 instruction

CONTROLLED


CROSSBAR IDENTIFICATION









VA crossbar



Steel Euro crossbar



HD crossbar

			FRONT CROSSBAR						REAR CROSSBAR					
					 VA	 Steel Euro	 HD				 VA	 Steel Euro	 HD	
Vehicle	Date	Crossbar	Front Right Pad/Clamp	Front Left Pad/Clamp	Measurement strip length per side	Measurement strip length per side	Measurement Distance (x)	Foot plate arrow direction	Rear Right Pad/Clamp	Rear Left Pad/Clamp	Measurement strip length per side	Measurement strip length per side	Measurement Distance (x)	Foot plate arrow direction
Hyundai i30 Hatch	17-	1180mm	M914 SUB0667	M913 SUB0667	213mm	N/A	994mm / 39, 1/8"	OUT	M567 SUB0667	M566 SUB0667	201mm	N/A	970mm / 38, 3/16"	OUT
			Pad Arrow OUT						Pad Arrow OUT					



Rhino Rack 2500 Series - DK492 instruction


Measurement A: CENTRE of door jamb to CENTRE arrow of leg foot plate.

Measurement B: CENTRE of Front leg foot plate arrow to CENTRE of Rear leg foot plate arrow.

Carrying capacity: Roof rack is rated up to 75kg. Please refer to manufacturers handbook for your vehicles maximum roof load capacity. Always use the lower of the two figures.


If your vehicle is not listed on this fitting instruction please refer to your countries Rhino-Rack web site for the latest information.

Direction of Pad Arrow and Foot Plate Arrow



FRONT

REAR



VEHICLE	Date	Measurement A	Measurement B	Load Rating up to (includes racks 5kg/ 11lbs)
Hyundai i30 Hatch	17-	225mm / 8,7/8"	700mm / 27,9/16"	75kg / 165lbs