


CROSSBAR IDENTIFICATION








VA crossbar



EURO crossbar



HD crossbar

			FRONT CROSSBAR						*REAR CROSSBAR*					
				 *VA*	 *EURO*	 *HD*				 *VA*	 *EURO*	 *HD*		
Vehicle	**Date**	**Crossbar**	**Front Right Pad/Clamp**	**Front Left Pad/Clamp**	**Measurement strip length per side**		**Measurement Distance (x)**	**Foot plate arrow direction**	**Rear Right Pad/Clamp**	**Rear Left Pad/Clamp**	**Measurement strip length per side**		**Measurement Distance (x)**	**Foot plate arrow direction**
RAM 1500 Quad Cab	19 -	1500	M282 SUB0155	M281 SUB0155	150mm	95mm	1188mm / 46 3/4”	OUT	M284 SUB0155	M283 SUB0155	143mm	88mm	1174mm / 46 1/4”	OUT
			FORWARD						FORWARD					
RAM 1500 Crew Cab	19 -	1500	M282 SUB0155	M281 SUB0155	150mm	95mm	1188mm / 46 3/4”	OUT	M284 SUB0155	M283 SUB0155	143mm	88mm	1174mm / 46 1/4”	OUT
			FORWARD						FORWARD					

Rhino Rack 2500 Series - DK504 instruction


Measurement A: CENTRE of door jamb to CENTRE arrow of leg foot plate.


Measurement B: CENTRE of Front leg foot plate arrow to CENTRE of Rear leg foot plate arrow.

Carrying capacity: Roof rack is rated up to 75kg. Please refer to manufacturers handbook for your vehicles maximum roof load capacity. Always use the lower of the two figures.

If your vehicle is not listed on this fitting instruction please refer to your countries Rhino-Rack web site for the latest information.

Direction of Pad Arrow and Foot Plate Arrow





VEHICLE	Date	Measurement A	Measurement B	Load Rating up to (includes racks 5kg/ 11lbs)
RAM 1500 Quad Cab	19 - on	310mm (12 3/16”)	650mm (25 9/16”)	75kg / 165lbs
RAM 1500 Crew Cab	19 - on	310mm (12 3/16”)	650mm (25 9/16”)	75kg / 165lbs